A METHOD AND SYSTEM FOR IMPLEMENTING A SERVICE IN A TELECOMMUNICATION SYSTEM

## FIELD OF THE INVENTION

The present invention relates to telecommunication. In particular, the present invention concerns

5    a method and system for implementing a service in a telecommunication system.

## BACKGROUND OF THE INVENTION

With the development of mobile communication

10   technologies, e.g. GSM technology, and intelligent network (IN) technology, the level of services provided by the public switched telephone network (PSTN) and public land mobile networks (PLMN) has risen considerably in recent years. The emergence of intelli-

15   gent network technologies allows the introduction of new services even within a short term. Before, a problem with the introduction of new services was that possible software updates had to be implemented in many or almost all telephone exchanges or mobile

20   switching centers (MSC).

With the intelligent network ideology, this problem has been partially eliminated. Some of the network components are "dumb" switching points which have no actual intelligence but are still capable of

25   identifying certain triggering factors associated with intelligent network services, thus directing service setup to other components. Therefore, "dumb" components can be used without major changes, thus allowing considerably faster introduction of new services.

30   The problem is, however, that services associated with call control, such as standardized GSM supplementary services, are still mostly implemented as permanent features in conjunction with call control, i.e. most services are directly encoded in the

35   call control logic of the switching center.

2

This will be a source of difficulties at the time of a future transition from standardized GSM supplementary services to a fully intelligent-network based service architecture. Specifically, there are

5   plans according to which the service architecture of the Universal Mobile Telecommunication System (UMTS) will be completely based on intelligent network technologies and will not comprise any standardized supplementary services.

10  The object of the present invention is to eliminate the drawbacks referred to above or at least to significantly alleviate them. A specific object of the invention is to disclose a new type of method and system in which services associated with call control

15  are not implemented as permanent elements of call control but instead as separate applications that use call control in a manner corresponding to intelligent network applications.

A further object of the invention is to dis-

20  close the use of call control and intelligent network interfaces in the implementation of standardized GSM supplementary services and especially a connection between a service control function (SCF) and the SSAP protocol (SSAP, Supplementary Services Application

25  Part). SSAP is a protocol used in the GSM network between two home location registers (HLR) or, against an ISDN network (ISDN, Integrated Services Digital Network), between a home location register and an ISDN switching center to synchronize the states of the two

30  queues - incoming and outgoing queues - in different network elements.

HLR is the home location register for a mobile station and it is used to store subscriber information, such as location data. Connected to a mobile

35  switching center is also a visitor location register (VLR), to which e.g. essential subscriber information is copied from the home location register.

As for the features characteristic of the invention, reference is made to the claims.

## BRIEF DESCRIPTION OF THE INVENTION

5      The method of the present invention concerns the implementation of a service in a telecommunication system comprising a mobile subscriber network, a mobile switching center connected to the mobile subscriber network and an intelligent network connected
10    to the mobile subscriber network. In the method, the mobile switching center is provided with a service control function, which is connected to the A-interface Call Control protocol, SSAP protocol and to a call control function, and a message received from a
15    protocol is transmitted to the service control function and the call control function is controlled by the service control function at the intelligent network interface. In this context, A-interface refers to the interface between a mobile station and a mobile
20    switching center. A Call Control protocol is a protocol used between a mobile switching center and a mobile station. The Call Control protocol used in the GSM system is RIL3-CC (RIL3-CC, Radio Interface Layer 3 Call Control). Moreover, in the method, the call
25    control function is used to make queries and receive instructions from the service control function.

       In a preferred embodiment of the present invention, a reference to the service control function is added to the call control triggering data if a
30    standardized GSM supplementary service whose functions can be implemented utilizing the intelligent network interface is active for the subscriber. Triggering data means "triggers" used to direct a desired service call to an appropriate place. Such triggering data may
35    consist of e.g. a given numeric sequence.

       In a preferred embodiment of the invention, the message transmitted from the service control func-

tion to the call control function is based on a method
or message of the call control function according to
e.g. CS-2, CAMEL Phase 3 or AIN call party handling.

5      In a preferred embodiment of the present in-
vention, at the beginning of a call, if any one of the
standardized GSM supplementary services implemented
via intelligent network interfaces is active for the
subscriber, data for the triggering of intelligent
network services are added to the subscriber informa-
10     tion obtained from the VLR and to the call control
function. In another preferred embodiment, the trig-
gering data are only added when the call control func-
tion queries the VLR for subscriber information in the
case of either an outgoing call or a terminating call.
15     In the triggering data, it is possible to include in-
formation regarding call control events in which it is
necessary to make a service control function query.
Moreover, in an embodiment, the intelligent network
interface for call control is an INAP interface.

20        The system of the invention for implementing
a service in a telecommunication system comprises a
mobile subscriber network, a mobile switching center
connected to the mobile subscriber network and an in-
telligent network connected to the mobile subscriber
25.    network. The mobile switching center in the system of
the invention is provided with a service control func-
tion. The service control function comprises means for
controlling the call control function at the intelli-
gent network interface. Moreover, the call control
30     function comprises means for making queries and means
for receiving instructions from the service control
function.

          In addition, the system comprises a home lo-
cation register connected to the mobile switching cen-
35     ter and a visitor location register  connected to the
mobile switching center. Further, the system of the
invention comprises an intelligent network switching

point connected to the mobile switching center of the mobile subscriber network and an intelligent network control point connected to the intelligent network switching point.

5      In a preferred embodiment of the invention, the mobile subscriber network is a digital land mobile network, e.g. a GSM network.

In a preferred embodiment of the invention, the service control function of the mobile switching

10    center is an internal program block in the mobile switching center, whose interface to the call control function, to the A-interface call control protocol or SSAP protocol is based on the communication method used between the program blocks in the mobile switch-

15    ing center.

In a preferred embodiment of the invention, the service control function of the mobile switching center communicates with the mobile switching center via a Corba (CORBA, Common Object Request Broker Ar-

20    chitecture) interface defined by OMG (Object Management Group). In this case, the connection with the call control, the A-interface call control protocol or the SSAP protocol is established via the Corba interface.

25.    The invention makes it possible to once implement in call control a functional mechanism that can be utilized both in the switching center's own services and in intelligent network services. Moreover, the invention can be used to implement various

30    present and future mobile network supplementary services.


LIST OF ILLUSTRATIONS

In the following, the invention will be described in detail by the aid of examples of its em-

35    bodiments, wherein

Fig. 1 presents a skeleton diagram showing
the components of a mobile communication system util-
izing an intelligent network that are essential with
regard to the invention.

5          Fig. 2 presents a system according to the
present invention,

Fig. 3 presents an embodiment of the present
invention as an example of a system for setting up a
CCBS call (CCBS, Call Completion to Busy Subscriber)

10   based on intelligent network architecture,

Fig. 4 presents an example of a flow diagram
illustrating the use of a system as presented in Fig.
3 in the case of a CCBS call,

Fig. 5 presents an embodiment of the present

15   invention as an example of a system for setting up a
CCBS call based on intelligent network architecture,

Fig. 6 presents a call setup chain in the
case of a CCBS call,

Fig. 7 presents an example of a flow diagram

20   illustrating the use of a system as presented in Fig.
5 in the case of a CCBS call,

Fig. 8 presents an embodiment of the present
invention as an example of a system for setting up a
CCBS call based on intelligent network architecture,

25 .        Fig. 9 presents a call setup chain in the
case of a CCBS call,

Fig. 10 presents a flow diagram exemplifying
the use of a system as presented in Fig. 8 in the case
of a CCBS call, and

30   Fig. 11 presents an example of a flow diagram
illustrating an embodiment of the invention.


DETAILED DESCRIPTION OF THE INVENTION

Fig. 1 is a diagrammatic representation of a

35   system according to the invention, comprising a mobile
subscriber network 1 and an intelligent network 3 con-
nected to it. Connected to the mobile subscriber net-

work 1 is a mobile switching center 2. The mobile
switching center 2 is provided with a separate service
control function 4. Moreover, the mobile switching
center comprises a call control function 5. The serv-
ice control function 4 comprises means 6 for control-
ling the call control function 5 at the intelligent
network interface. Further, the call control function
5 comprises means 7 for making queries to obtain in-
formation from the service control function 4 and
means 8 for receiving instructions from the service
control function 4. Connected to the mobile switching
center 2 are also a home location register 10 and a
visitor location register 11. Further, connected via a
radio interface to the mobile switching center is a
first telecommunication terminal 14, which in this ex-
ample is a mobile station.

In this example, the intelligent network 3
comprises an intelligent network service switching
point 12 (SSP) and an intelligent network service con-
trol point 13 (SCP) connected to the intelligent net-
work service switching point 12. For the transfer of
information between the SSP 12 and SCP 13, the INAP
protocol (INAP, Intelligent Network Application Part)
is used. INAP is a protocol stack connecting common
channel signalling to an intelligent network.

Connected to the mobile subscriber network 1
and intelligent network 3 in this example is also a
wired telephone network 9 (Public Switched Telephone
Network). Further, connected to the wired telephone
network 9 is a second telecommunication terminal 15.

Means 6 - 8 are implemented in a manner known
in itself, e.g. as program blocks used by computer,
and they will therefore not be described in detail.

Fig. 2 presents an embodiment of the system
of the present invention according to Fig. 1. The sys-
tem comprises an intelligent network control function
SCF, which is connected via an INAP interface to an

intelligent network service switching function (SSF).
Connected to the service switching function SSF is
also a call control function CCF. Also connected to
the service switching function is the service control
5   function of the mobile switching center MSC-SCF via
the intelligent network interface. The MSC-SCF is op-
erated by program block PRB X (PRB, ProgRam Block).

The GSM network service control function MSC-
SCF consists of separate components GSM SLP (SLP,
10  Service Logic Program) and GSM SLEE (SLEE, Service
Logic Execution Environment). The actual service logic
is located in the SLP. The SLPs are run in a SLEE en-
vironment. The SLEE contains e.g. an operating system,
external modules or program libraries. In a preferred
15  embodiment of the invention, the SLEE is an execution
environment based on Sun Microsystems Java language.

Fig. 3 presents a preferred embodiment of the
system of the present invention. The system illus-
trated in Fig. 3 represents a system based on intelli-
20  gent network architecture, designed to implement a
CCBS service. The system comprises a home location
register HLR A (HLR, Home Location Register), which
communicates with the MSC-SCF via a MAP interface
(MAP, Mobile Application Part). In addition, the sys-
25  tem comprises an SSF and a CCF, which communicate with
the MSC-SCF via an INAP interface. In this example,
the MSC-SCF, SSF and CCF together form the mobile
switching center MSC-A of the mobile subscriber net-
work. A CCSB call begins when the HLR-A for the A-
30  subscription announces that the B-party is on-hook. A
CCBS RUF message (RUF, Remote User Free) indicates
that the HLR for the B-party has reported that the B-
party is free. The RUF message is transmitted via the
HLR-A to the MSC-A, whereupon the MSC-A starts call
35  setup from the A-party to the B-party. The MSC-SCF
sets up a CCBS call by utilizing the CS-2 properties
(CS-2, Capability Set 2) of the intelligent network.

Fig. 4 presents an example illustrating the operation of a system according to Fig. 3 in the case of a CCBS call. As shown in the figure, the MSC-A starts call setup to establish a call to MS-A (MS, Mo-
5    bile Station). Once the call setup procedure has been successfully completed, the MSC-A sets up a speech connection to the B-party in a corresponding manner. In this example, the B-party is a subscriber in the wired telephone network PSTN.

10    Fig. 5 presents a preferred embodiment of the present invention as an example of the system of the invention. In this example, the CS-2 properties of the intelligent network are utilized. The system comprises an SSF and a CCF, which communicate with the MSC-SCF
15    via an INAP interface. In this example, the MSC-SCF, SSF and CCF together form the mobile switching center MSC-A of the mobile subscriber network. Concepts p1 and p2 appearing in the figure signify A- and B-parties.

20    Fig. 6 presents a preferred example of a call setup scheme according to the present invention in conjunction with a CCBS call. In this example, the CS-2 properties of the intelligent network are utilized. The call is set up in a system as presented in Fig. 5.
25    From the Null state, the network starts call setup ICA (ICA, InitiateCallAttempt) in the A-party's direction (1-party setup). Next, the A-party is authenticated (call setup authorization). When the A-party answers, the result is a stable 1-party state, whereupon call
30    setup is continued in the B-party's direction. After the B-party has been authenticated, a call between the A- and B-parties can be established.

Fig. 7 presents an example of the operation of the system according to Fig. 5 in the case of a
35    CCBS call. The CS-2 properties of the intelligent net-work are utilized in this example. Call setup is ef-fected as in Fig. 6. The MSC-SCF starts call setup by

sending an ICA message to the SSF. After the A-party
has answered, the MSC-SCF inquires via a notice and
collection of a DTMF selection whether the A-party ac-
cepts the call initiation. After the A-party has ac-

5    cepted the call initiation in the B-party's direction,
the MSC-SCF starts call setup to the B-party by per-
forming a connect operation. A connection between the
A- and B-parties is established if the B-party an-
swers.

10          Fig. 8 presents an example of a preferred em-
bodiment of the system of the present invention. In
this example, the CS-2 properties of the intelligent
network are utilized. The system comprises an SSF and
a CCF, which communicate with the MSC-SCF via an INAP

15   interface. In this example, the MSC-SCF, SSF and CCF
together form the mobile switching center MSC-A of the
mobile subscriber network.

            Fig. 9 presents a preferred example of opera-
tion according to the invention in conjunction with a

20   CCBS call. In this example, the CS-2 properties of an
intelligent network are utilized. The call is set up
in a system as illustrated in Fig. 8. From the Null
state, the network starts call setup in the direction
of the A-party (1-party setup). After the A-party has

25   answered, the state changes to a Stable 1-party state,
whereupon the A-party accepts the call initiation. Af-
ter this, a second call is initiated (ICA) in the di-
rection of the B-party. After the B-party has answered
(answer), these two calls are connected together via

30   an MCS operation (MCS, MergeCallSegments), a transfer
state being thus reached.

            Fig. 10 presents an example of the operation
of the system according to Fig. 8 in the case of a
CCBS call. In this example, the CS-2 properties of an

35   intelligent network are utilized. Call setup is ef-
fected in accordance with Fig. 9. The MSC-SCF starts
call setup by sending an ICA message to the SSF. After

the A-party has been authenticated (call setup auth.),
the MSC-SCF starts call setup to the B-party by send-
ing an ICA message to the SSF. The two calls are con-
nected together when the MSC-SCF sends an MCS message
5    to the SSF.

        Fig. 11 presents a preferred example of a
flow diagram representing the operation of the system
of the invention. According to block 16, the A-party
starts call setup by dialling a desired number. The
10   telecommunication terminal used by the A-party is
preferably a mobile station. In conjunction with the
location updating procedure, the internal service con-
trol function examines the subscriber's service data
obtained from the home location register HLR and, if
15   any one of the above-mentioned services is active for
the subscriber, changes the intelligent network trig-
gering data to be stored in the visitor location reg-
ister VLR and given to the call control function at
the beginning of the call. The triggering data are
20   changed by adding to them an indication of the events
in call control function that require an internal con-
trol function query. In other words, if the numeric
data selected by the A-party functions as a triggering
factor, then call control is transferred to the inter-
25.  nal service control function and messages related to
service requests are directed to the internal service
control function (block 17). The internal service con-
trol function controls the call control function by
using the intelligent network interface for call con-
30   trol (block 18), thus taking care of implementing the
desired service.

        Let it be further stated that the invention
has been mainly described with reference to the GSM
system (GSM, Global System for Mobile communications)
35   and using associated terms, but the invention can also
be used or applied in some other mobile communication
system.

The invention is not restricted to the examples of its embodiments described above, but many variations are possible within the scope of the inventive idea defined in the claims.